

PROJECT FLOORS

the up-to-date company

*light*²
THE LIFESTYLE COLLECTION

Covering Type According to DIN 16951	Heterogeneous Plankwood	Heterogeneous Tiles
Number of Colours	16	4
Packaging per Box/Pallet	3.34m ² /240.48m ²	3.34m ² /240.48m ²
Performance classification EN 685	21-23, 31	21-23, 31
Total thickness EN 428	2.0mm	2.0mm
Wear layer thickness EN 429	0.3mm	0.3mm
Surface treatment	yes / PU	yes / PU
Beveled PU Edges	No	No
Total weight EN 430	3.8kg/m ²	3.8kg/m ²
Residual indentation EN 433	0.05mm	0.05mm
Castor chair suitability EN 425	Suitable for castor chairs in acc. With DIN 68131, Type W	Suitable for castor chairs in acc. With DIN 68131, Type W
Under floor heating	Suitable	Suitable
Behaviour to fire Din 4102	B1	B1
Impact sound improvement DIN 52210	4dB	4dB
Colour fastness DIN 53389	> 6	> 6
Electrostatic characteristics DIN 51953	> 1010	> 1010
Chemical resistance DIN 51958	present *	present *
Slip resistance	R9	R9
Adhesive Recommendation	ProjectBond	
Maintenance/Cleaning recommendation	See separate installation instructions	See separate installation instructions

www.projectfloors.co.nz