

PROJECT FLOORS

the up-to-date company



Luxury, high performance PVC-floor covering
for commercial application

Covering Type According to DIN 16951	Heterogeneous Plankwood	Heterogeneous Tiles
Number of Colours	54	35
Packaging per Box/Pallet	3.34m ² /187.04m ²	3.34m ² /180.36m ²
Performance classification EN 685	23, 34, 43 (K5)	23, 34, 43 (K5)
Total thickness EN 428	2.5mm	2.5mm
Wear layer thickness EN 429	0.8-1.0mm	0.8-1.0mm
Surface treatment	yes	yes
Beveled PU Edges	yes	yes
Total weight EN 430	4.8kg/m ²	4.8kg/m ²
Residual indentation EN 433	0.05mm	0.05mm
Castor chair suitability EN 425	Suitable for castor chairs in acc. With DIN 68131, Type W	Suitable for castor chairs in acc. With DIN 68131, Type W
Under floor heating	Suitable	Suitable
Behaviour to fire Din 4102	B1	B1
Impact sound improvement DIN 52210	4dB	4dB
Colour fastness DIN 53389	> 6	> 6
Electrostatic characteristics DIN 51953	> 1010	> 1010
Chemical resistance DIN 51958	present *	present *
Slip resistance	R9	R9
Adhesive recommendation	ProjectBond	
Maintenance/Cleaning recommendation	See separate installation instructions	See separate installation instructions

www.projectfloors.co.nz