



1

PROJECTSTIK Carpet Tile Adhesive

Description:

ProjectStik is a solvent free non-staining, pure acrylic dispersion, designed to provide a permanently tacky film for the installation of Project Floors PVC & EcoTex backed Carpet Tiles.

Surface Preparation:

To be in accordance with:

1. The Australian Standard 1884-1985 "Floor Coverings - Resilient Sheet and Tiles - Laying and Maintenance Practices"
2. The Australian Standard 2455.1:1995 "Textile Floor Covering - Installation Practice".

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease & hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive application is 10 degrees C.

It is recommended that all wooden or concrete subfloor surfaces be primed with Project-Primer prior to the application of adhesive. All concrete substrate floors should be tested for moisture content, according to the above Australian Standard, prior to undertaking surface priming or installation of floorcovering.

Technical Data:

Appearance: Milky White
Base: Pure Acrylic
Flammability: Non-flammable (water based)
Toxicity: Non Toxic
S.G.: Approximately 1.02
Tack-up: Typically 15-30 minutes (but may be longer), depending on temperature, floor Absorbency, humidity and application weights.

Application:

Adhesive should be applied with a 1.0mm - 1.5mm V notched trowel dependant on the porosity of the surface to be adhered to. This will give a strong aggressive bond. Allow adhesive film to dry clear. The adhesive is now in a dry tack mode, and the carpet tile may be placed in position. Best bonds will be achieved by placing the tiles into the adhesive, as soon as possible after the film has cleared. It is not good practice to leave adhesive exposed to possible contaminants, such as dust, for long periods of time.

Coverage:

Approximately 7-10 m²/litre depending on the condition and absorbency of the floor, and the application method used.

Clean Up:

Any Project-Stick on the surface of floorcovering should be removed as soon as possible with a well dampened cloth. Once dry, the product is extremely tenacious and will trap dirt. Dried adhesive may be removed with Acetone. Note: Before using any cleaner, first establish cleaner will not damage the carpet tile.

Shelf Life/Storage:

12 months minimum, in unopened containers stored between 5°C and 25°C. Keep in a well ventilated area away from direct heat sources and sunlight.

First Aid:

If poisoning occurs contact a doctor or Poisons Information Centre. If swallowed, DO NOT induce vomiting. Give a glass of water.

Material Safety Data Sheet available on request.

Contact Details

Ph: 09 4444 165
Fax: 09 4444 135
Mobile: 021 275 9393 / 021 952 339 / 021 954 339
021 851 339 / 021 932 839
E-mail: info@projectfloors.co.nz